

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0.97$ (W/m²K)

Please consult typology, dimensions and glazing

ACCUSTIC INSULATION

Maximum glazing: **45 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Water tightness (EN 12208):

Wind resistance (EN 12210):

Reference test: 2.700 x 2.530 mm / 3 sashes

Security test: **PAS24** ☒

Configuration 330. 2701 x 2517 mm / 3 sashes

Class 4

Class 9A

Class A3

Passed

SECTIONS	Frame 73 mm Sash 73 mm
PROFILE THICKNESS	Door 1.8 mm
MAXIMUM DIMENSIONS	Width (L) = 1.200 mm Height (H) = 3.000 mm
MAXIMUM WEIGHT/SASH	120 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
----------	---

EXTRUSION ALLOY	6063 T-5
POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: Frame 20 mm Sash 30 mm

OPENING POSSIBILITIES	Inward: 1 to 14 sashes Outward: 1 to 14 sashes Possibility of corner sash at 90° without mullion
ACCESSIBILITY	Possibility of embedded low threshold

